



Eslinga de cadena Modelo 5

Información del producto

Working load limit (tons) - chain G8 Ø chain mm	Working load limit (tons) - chain G8 1 leg 0° Factor 1,0	Working load limit (tons) - chain G8 2 legs 0° < β ≤ 45° Factor 1,4	Working load limit (tons) - chain G8 2 legs 45° < β ≤ 60° Factor 1,0	Working load limit (tons) - chain G8 3 - 4 legs 0° < β ≤ 45° Factor 2,1	Working load limit (tons) - chain G8 3 - 4 legs 45° < β ≤ 60° Factor 1,5	Working load limit (tons) - chain G8 Endless slipknot Factor 1,6	Working load limit (tons) - chain G8 1 leg choker Factor 0,8	Working load limit (tons) - chain G8 Legs choker: 1 sling 2 legs 0° < β ≤ 45° Factor 1,1	Working load limit (tons) - chain G8 Simple basket: sling 1 leg (link+hook) 0° < β ≤ 45° Factor 1,0	Working load limit (tons) - chain G8 Simple basket: sling 1 leg (2 links) 0° < β ≤ 45° Factor 1,4	Working load limit (tons) - chain G8 Doble basket: sling 2 legs (link+hook) 0° < β ≤ 45° Factor 1,4	Working load limit (tons) - chain G8 Doble basket: sling with triple link 0° < β ≤ 45° Factor 2,1	Total price
6	1,12	1,60	1,12	2,36	1,70	1,80	0,90	1,23	1,12	1,60	1,60	2,36	N/A
7	1,50	2,12	1,50	3,15	2,24	2,50	1,20	1,65	1,50	2,12	2,12	3,15	N/A
8	2,00	2,80	2,00	4,25	3,00	3,15	1,60	2,20	2,00	2,80	2,80	4,25	N/A
10	3,15	4,25	3,15	6,70	4,75	5,00	2,52	3,47	3,15	4,25	4,25	6,70	N/A
13	5,30	7,50	5,30	11,2	8,00	8,50	4,24	5,83	5,30	7,50	7,50	11,2	N/A
16	8,00	11,2	8,00	17,0	11,8	12,5	6,40	8,80	8,00	11,2	11,2	17,0	N/A
19	11,2	16,0	11,2	23,6	17,0	18,0	8,96	12,3	11,2	16,0	16,0	23,6	N/A
22	15,0	21,2	15,0	31,5	22,4	23,6	12,0	16,5	15,0	21,2	21,2	31,5	N/A
26	21,2	30,0	21,2	45,0	31,4	33,5	17,0	23,3	21,2	30,0	30,0	45,0	N/A
32	31,5	45,0	31,5	67,0	47,5	50,0	25,2	34,7	31,5	45,0	45,0	67,0	N/A