

Terminal cónico cerrado Ropeblock CSS

Información del producto



The Ropeblock closed spelter socket CSS designed with mechanical values (Charpy-V > 42 joule / - 20° C) for tough and low temperature use. All sockets have a 100% efficiency on the MBL of the steel wire rope but are limited to the MBL of the socket.

The CSS sockets are Type Approved by DNV and Lloyd's Register.

CSS 296 until CSS 201 only available with hot dipped galvanized finish
... [Más información](#)

Marcado: CE-marked

Terminal cónico cerrado Ropeblock CSS

Plano



Datos técnicos

| Referencia CYE | Diámetro del cable mm | Fuerza mínima de rotura MBL ton | Finish | Strand Ø mm | A mm | B mm | C mm | Ø H mm | K mm | T mm | TA mm mm | TL mm mm | Peso kg |
|----------------|--------------------------|------------------------------------|------------|----------------|------|------|------|--------|------|------|----------|----------|------------|
| Y6ATECSS296G | 6-7 | 8 | Galvanized | - | 50 | 40 | 11 | 9,1 | 22 | 13 | 37 | 101 | 0,3 |
| Y6ATECSS297G | 8-10 | 12 | Galvanized | - | 57 | 48 | 14 | 12,6 | 25 | 18 | 43 | 119 | 0,5 |
| Y6ATECSS298G | 11-13 | 20 | Galvanized | - | 64 | 59 | 17,5 | 14,6 | 30 | 23 | 51 | 140 | 0,7 |
| Y6ATECSS299G | 14-16 | 25 | Galvanized | 13 | 76 | 65 | 21 | 18,1 | 36 | 26 | 67 | 162 | 1,4 |
| Y6ATECSS200G | 18-19 | 40 | Galvanized | 14-16 | 89 | 78 | 27 | 21,9 | 42 | 32 | 76 | 194 | 2,2 |
| Y6ATECSS201G | 20-22 | 55 | Galvanized | 18-19 | 101 | 90 | 33 | 24,9 | 47 | 38 | 92 | 224 | 3,8 |
| Y6ATECSS204y | 23-26 | 75 | Galvanized | 20-22 | 114 | 103 | 36 | 28,8 | 57 | 44 | 104 | 253 | 5,4 |
| Y6ATECSS204y | 23-26 | 75 | Painted | 20-22 | 114 | 103 | 36 | 28,8 | 57 | 44 | 104 | 253 | 5,4 |
| Y6ATECSS207y | 27-30 | 90 | Galvanized | 23-26 | 127 | 116 | 39 | 32,9 | 65 | 51 | 114 | 282 | 7 |
| Y6ATECSS207y | 27-30 | 90 | Painted | 23-26 | 127 | 116 | 39 | 32,9 | 65 | 51 | 114 | 282 | 7 |
| Y6ATECSS212y | 31-36 | 125 | Galvanized | 27-28 | 139 | 130 | 43 | 39,2 | 71 | 57 | 126 | 312 | 10 |
| Y6ATECSS212y | 31-36 | 125 | Painted | 27-28 | 139 | 130 | 43 | 39,2 | 71 | 57 | 126 | 312 | 10 |
| Y6ATECSS215y | 37-39 | 150 | Galvanized | 30-32 | 152 | 155 | 51 | 42,5 | 81 | 63 | 136 | 358 | 13 |
| Y6ATECSS215y | 37-39 | 150 | Painted | 30-32 | 152 | 155 | 51 | 42,5 | 81 | 63 | 136 | 358 | 13 |
| Y6ATECSS217y | 40-42 | 170 | Galvanized | 33-35 | 165 | 171 | 54 | 45,5 | 83 | 70 | 146 | 390 | 17 |
| Y6ATECSS217y | 40-42 | 170 | Painted | 33-35 | 165 | 171 | 54 | 45,5 | 83 | 70 | 146 | 390 | 17 |
| Y6ATECSS219y | 43-48 | 225 | Galvanized | 36-40 | 190 | 198 | 55 | 52,5 | 93 | 76 | 171 | 443 | 26 |
| Y6ATECSS219y | 43-48 | 225 | Painted | 36-40 | 190 | 198 | 55 | 52,5 | 93 | 76 | 171 | 443 | 26 |
| Y6ATECSS222y | 49-54 | 280 | Galvanized | 42-45 | 216 | 224 | 62 | 59,1 | 100 | 82 | 193 | 502 | 37 |
| Y6ATECSS222y | 49-54 | 280 | Painted | 42-45 | 216 | 224 | 62 | 59,1 | 100 | 82 | 193 | 502 | 37 |
| Y6ATECSS224y | 55-60 | 360 | Galvanized | 46-48 | 228 | 247 | 73 | 65,1 | 112 | 92 | 216 | 548 | 50 |
| Y6ATECSS224y | 55-60 | 360 | Painted | 46-48 | 228 | 247 | 73 | 65,1 | 112 | 92 | 216 | 548 | 50 |

Terminal cónico cerrado Ropeblock CSS

Datos técnicos

| Referencia CYE | Diámetro del cable mm | Fuerza mínima de rotura MBL ton | Finish | Strand Ø mm | A mm | B mm | C mm | Ø H mm | K mm | T mm | TA mm mm | TL mm mm | Peso kg |
|----------------|--------------------------|------------------------------------|------------|----------------|------|------|------|--------|------|------|----------|----------|------------|
| Y6ATECSS226y | 61-68 | 425 | Galvanized | 50-54 | 248 | 270 | 79 | 73,4 | 140 | 102 | 241 | 257 | 66 |
| Y6ATECSS226y | 61-68 | 425 | Painted | 50-54 | 248 | 270 | 79 | 73,4 | 140 | 102 | 241 | 257 | 66 |
| Y6ATECSS227y | 69-75 | 460 | Galvanized | 56-62 | 279 | 286 | 79 | 79,4 | 159 | 124 | 273 | 644 | 91 |
| Y6ATECSS227y | 69-75 | 460 | Painted | 56-62 | 279 | 286 | 79 | 79,4 | 159 | 124 | 273 | 644 | 91 |
| Y6ATECSS228y | 76-80 | 560 | Galvanized | 64-67 | 315 | 298 | 83 | 88,2 | 171 | 133 | 292 | 696 | 117 |
| Y6ATECSS228y | 76-80 | 560 | Painted | 64-67 | 315 | 298 | 83 | 88,2 | 171 | 133 | 292 | 696 | 117 |
| Y6ATECSS229y | 81-86 | 625 | Galvanized | 69-76 | 330 | 311 | 102 | 92,4 | 184 | 146 | 311 | 743 | 125 |
| Y6ATECSS229y | 81-86 | 625 | Painted | 69-76 | 330 | 311 | 102 | 92,4 | 184 | 146 | 311 | 743 | 125 |
| Y6ATECSS230y | 87-93 | 720 | Galvanized | 78-86 | 356 | 330 | 102 | 98,8 | 197 | 159 | 330 | 788 | 176 |
| Y6ATECSS230y | 87-93 | 720 | Painted | 78-86 | 356 | 330 | 102 | 98,8 | 197 | 159 | 330 | 788 | 176 |
| Y6ATECSS231y | 94-102 | 875 | Galvanized | 88-96 | 381 | 356 | 108 | 107,8 | 216 | 178 | 362 | 845 | 228 |
| Y6ATECSS231y | 94-102 | 875 | Painted | 88-96 | 381 | 356 | 108 | 107,8 | 216 | 178 | 362 | 845 | 228 |
| Y6ATECSS233y | 108-115 | 1.200 | Galvanized | 98-110 | 450 | 425 | 125 | 129,5 | 235 | 190 | 405 | 1.000 | 323 |
| Y6ATECSS233y | 108-115 | 1.200 | Painted | 98-110 | 450 | 425 | 125 | 129,5 | 235 | 190 | 405 | 1.000 | 323 |
| Y6ATECSS240y | 120-130 | 1.400 | Galvanized | 112-124 | 500 | 525 | 125 | 147,1 | 260 | 200 | 450 | 1.150 | 447 |
| Y6ATECSS240y | 120-130 | 1.400 | Painted | 112-124 | 500 | 525 | 125 | 147,1 | 260 | 200 | 450 | 1.150 | 447 |
| Y6ATECSS245y | 135-140 | 1.600 | Galvanized | 125-132 | 540 | 495 | 150 | 153,9 | 290 | 220 | 520 | 1.185 | 645 |
| Y6ATECSS245y | 135-140 | 1.600 | Painted | 125-132 | 540 | 495 | 150 | 153,9 | 290 | 220 | 520 | 1.185 | 645 |
| Y6ATECSS250y | 142-153 | 2.000 | Galvanized | 133-143 | 585 | 530 | 170 | 171,1 | 305 | 240 | 545 | 1.285 | 741 |
| Y6ATECSS250y | 142-153 | 2.000 | Painted | 133-143 | 585 | 530 | 170 | 171,1 | 305 | 240 | 545 | 1.285 | 741 |
| Y6ATECSS255y | 154-165 | 2.220 | Galvanized | 144-154 | 630 | 565 | 175 | 185,1 | 330 | 250 | 575 | 1.370 | 860 |
| Y6ATECSS255y | 154-165 | 2.220 | Painted | 144-154 | 630 | 565 | 175 | 185,1 | 330 | 250 | 575 | 1.370 | 860 |
| Y6ATECSS260y | 166-178 | 2.500 | Galvanized | 155-166 | 680 | 590 | 180 | 199,1 | 330 | 270 | 595 | 1.450 | 985 |
| Y6ATECSS260y | 166-178 | 2.500 | Painted | 155-166 | 680 | 590 | 180 | 199,1 | 330 | 270 | 595 | 1.450 | 985 |
| Y6ATECSS265y | 180-191 | 2.800 | Galvanized | 167-179 | 725 | 620 | 190 | 213 | 350 | 290 | 625 | 1.535 | 1.183 |
| Y6ATECSS265y | 180-191 | 2.800 | Painted | 167-179 | 725 | 620 | 190 | 213 | 350 | 290 | 625 | 1.535 | 1.183 |
| Y6ATECSS270y | 192-204 | 3.200 | Galvanized | 180-191 | 775 | 650 | 210 | 228,5 | 395 | 305 | 690 | 1.635 | 1.487 |
| Y6ATECSS270y | 192-204 | 3.200 | Painted | 180-191 | 775 | 650 | 210 | 228,5 | 395 | 305 | 690 | 1.635 | 1.487 |